



Discover more details and matching accessories online!

## Moisture analyser with high-quality single-cell weighing system for outstanding stability, reliability and response speed

### Features

- Tip: Suitable for samples with low moisture content, e.g. plastics
- Backlit graphic display, digit height 15 mm
- 1 Active drying process
- 2 Previous drying time
- 3 Current temperature
- 4 Unit for displaying the results
- 5 Current moisture content in %
- 6 Active heating profile

- 400 W halogen-quartz glass heater
- Excellent temperature control thanks to halogen technology, suitable for temperature-sensitive samples
- Internal memory for automatic sequence of 10 complete drying processes and 100 drying processes carried out
- The last measured value remains visible in the display until the next measurement
- Password protection to prevent manipulation of stored settings, data, etc.

- Sample description for up to 99 samples, freely programmable, and is printed in the measuring protocol
- Date and time display as standard
- USB data interface for transferring weighing data to the PC, printer etc.
- 50 sample plates included
- Protective working cover included with delivery
- On the internet, you will find a practical application handbook containing many examples, field reports, settings and tips for each KERN moisture analyser

### STANDARD



### OPTION



KERN	DBS 60-3
Readability [d] Weight/Moisture (%)	0,001 g / 0,01 %
Weighing capacity [Max]	60 g
Reproducibility weight of sample 2 g*	0,15 %
Reproducibility weight of sample 10 g*	0,02 %
Display after drying	
Moisture [%] = Moisture content (M) from wet weight (W)	0,1 % - 100 %
Dry content [%] = Dry weight (D) from (W)	100 % - 0,1 %
ATRO [%] [(W-D) : D] · 100 %	0 - 999 %
Moisture content (M)	Absolute value in [g]
Temperature range (in steps up to)	50 °C - 200 °C (1 °C)
Drying modes	Standard drying, Drying in levels, Gentle drying, Rapid drying Automatic unrestricted switch-off (Selectable loss in weight 0,01 % - 0,1 % in 30 s) Time controlled switch-off (1 min - 12 h) Manual switch-off at the press of a button
Switch-off criteria	
Recall of measurement/ Log output	Interval can be set from 1 s - 10 min (Only when used with printer or PC)
Overall dimensions W×D×H	204×336×167 mm
Net weight	4,6 kg
Option Calibr. Certificate DAkkS accr.   Mass	963-127
Option Factory calibration certificate   Temperature	964-305

\* dépendant de l'application